

BlueTruckMaster®

Portable AdBlue® storage and dispensing solutions

Available from 200 to 900 litres



Portable AdBlue® storage and dispensing solutions

Available from 200 to 900 litres

The Kingspan BlueTruckMaster® range is specifically designed for the safe transportation of AdBlue®. This portable and robust solution means users can easily refuel their vehicles on or off site.

BlueTruckMaster® tanks are made from high-quality polyethylene, and are specifically designed to resist mechanical shocks and their impact, extreme and variable weather conditions, and UV radiation - all whilst offering a wide range of options to satisfy all users.

BTM430/300 Equipment Specification

1. Tank
2. Pump
3. Automatic nozzle
4. Ventilation
5. Delivery hose
6. Lockable lid*
7. Shackles**
8. Filler opening**

* Lid with integrated lock (BTM200 low profile, BTM430 and BTM900). BTM200 & BTM300 versions can be closed using a padlock (not provided).

** Only available on certain models.



Model Selector

All dimensions and weights are an approximation only

BTM200






Capacity	200 litres
Length	600 mm
Width	800 mm
Height	620 mm
Weight	33 kg

BTM200 low profile



Capacity	200 litres
Length	1180 mm
Width	860 mm
Height	500 mm
Weight	52 kg

BlueTruckMaster®

Easily transported	40 years' experience	Tank guarantee*
		

Standard Equipment:

- Semi-transparent PE tank with internal baffle wall
- Lockable lid
- Gas struts to help open the lid*
- Suction line with filter to keep the liquid clean
- 12 V DC self-priming pump
- 4 m delivery hose with automatic nozzle
- Automatic air vent valve
- Threaded filling point

Optional Equipment:

- 24 V DC self-priming pump
- 230 V AC self-priming pump
- Digital flowmeter to control the amount of liquid dispensed
- Battery-powered LED to facilitate use in the dark
- Lifting shackles
- Manual nozzle

Quality design and product reliability

Kingspan designs and manufactures innovative systems to stock, dispense and protect AdBlue® for customers the world over, whilst providing high-quality customer service. BlueTruckMaster® is a robust and reliable product that comes with a 5 year guarantee.

Excellent return on investment

Lightweight, portable storage solution offering a faster and safer delivery of AdBlue® to any point of use. Model options which occupy only half a euro pallet – saving you valuable time and money.

Portable solutions

The BlueTruckMaster® has been designed to go anywhere and to withstand the toughest of site conditions offering liquid delivery a new mobility. Additionally, the unique internal baffle wall minimises spillage when in transit - protecting AdBlue® and the environment.

Features:

- Specially designed tank for easy installation on a vehicle using transportation straps
- Integrated bulkhead reduces movement of liquid during transportation
- Lockable lid to prevent unauthorised persons accessing the tank equipment
- Integrated pump to facilitate quick refuelling
- Automatic nozzle to protect against overflowing when refuelling
- Ability to deliver AdBlue® to a precise location
- Wide range of pumps to adapt to different electrical power supply options
- 5 year tank guarantee and 2 years on parts
- After-sales service
- High-quality parts designed to store Adblue® for long periods of time



* Option, only BTM900

** 5 year tank guarantee and 2 years on parts

BTM300



Capacity	300 litres
Length	600 mm
Width	800 mm
Height	890 mm
Weight	45 kg

BTM430



Capacity	430 litres
Length	1180 mm
Width	860 mm
Height	910 mm
Weight	64 kg

BTM900



Capacity	900 litres
Length	1410 mm
Width	1050 mm
Height	1210 mm
Weight	97 kg

Specification Options

Data sheets are available for each of the specification options below.

BlueTruckMaster®

Description / Capacity	BTM200	BTM300	BTM200 low profile	BTM430	BTM900
Ball valve on suction line					•
Suction line with mesh filter	•	•	•	•	•
12 V DC pump (max. flow rate 50 l/min)	•	•	•	•	•
6 m power cable with battery clamps	•	•	•	•	•
4 m flexible delivery hose	•	•	•	•	•
Automatic nozzle	•	•	•	•	•
Lid with integrated lock			•	•	•
Lid with lockable latch (padlock not provided)	•	•			
Vacuum and pressure relief valve	•	•	•	•	•
Lid with support gas struts					•
4 lifting shackles			○	○	○
Battery powered LED lamp			○	○	○
24 V DC pump (max. flow rate 50 l/min)	○	○	○	○	○
230 V AC pump (max. flow rate 56 l/min)			○	○	○
Digital flowmeter fixed to the delivery nozzle	○	○	○	○	○

● Standard accessories ○ Optional accessories

Visit www.kingspan.com to find out more about our products and services, in over 40 countries.

UK
kingspan.co.uk
tankinfo@kingspan.co.uk

France
kingspan.fr
cuve@kingspan.fr

Ireland
kingspan.ie
tankinfo@kingspan.ie

Belgium
kingspan.be
info@kingspan-env.be

Netherlands
kingspan.nl
tank@kingspan.nl

Germany
kingspan.de
tank@kingspan.de

Sweden
kingspan.se
tank@kingspan.se

Czech Republic
kingspan.cz
nadrze@kingspan.cz

Poland
kingspan.pl
zbiorniki@kingspan.pl

Finland
kingspan.fi
tankinfo@kingspan.com

Global Head Office:
180 Gilford Road
Portadown
Co. Armagh
BT63 5LF United Kingdom
T: +44 (0) 28 3836 4444

European Office:
ul. Topolowa 5
62-090 Rokietnica
Poland
T: +48 61 814 44 00